



Product Name	Part No
24 FIBER MPO (M) LC SINGLE MODE HD CASSETTE BOX FOR HD ODF	JTMPS224MOSMLCPB

Description

24F MPO Cassette Modules are fitted with 24 Fibers SM breakout cable and have LC adapters on the front side and MPO Adaptor at the rear. This cassette is made into smaller size and can be deployed in an ODF. JTOPTICS MPO Cassette Modules reduce the overall cost and setup time for complex high density networking used in data center application.

Key Features

- High density pre-terminated fiber optic system
- Complied to ANSI/TIA-568-C.3, IEEE 802.3ba and adheres to ANSI/TIA-942
- Aluminum alloy shell protect the inner fibers effectively
- High-quality MPO connectors and guaranteed by 3D interferometer
- Small Design and Compatible with FHD Fiber Enclosures

Application

- HD Data Center Cabling Management.
- Telecom
- Enterprise Network
- Data Center Infrastructure

Rear Connector Type	MPO Male (24 Fiber)	Front Connector Type	12 X LC PC Duplex
Fiber Mode	OS2 SMF 9/125µm	Wavelength	1310/1550nm
MPO Connector IL	0.35dB Max	LC Connector IL	≤0.2dB
MPO Connector RL	≥60dB	LC Connector RL	≥50dB
Dimension (HxWxD)	35x109x118mm	MPO Adapter	Key up to Key down
Storage Temperature	-40°C to +85°C	Operating Temperature	-10°C to +70°C
Connector Make	JTOPTICS / NISSIN	Connector Quality	Standard

