

Product Name	Part No
24 Port liu fms patch panel rack mount slidinng type with lc pc multi mode adaptor, splice tray and pigtail	JTPP24RSLCPM

### Description

Optical sliding Patch Panel is a kind of fiber optic management products used to distribute and protect the optical fiber links in fiber optical Network. It is available for the distribution and terminal connection of various kinds of optical fiber system. These units are available in sizes that fit the most common distribution requirements. Our Patch panel has been designed to accept up to 48 fibers housed within a 1U space and up to 96 fiber in 2U space.

- |              |  |
|--------------|--|
| FEATURES     | <ul style="list-style-type: none"> <li>• 19" standard mounting design, nice appearance</li> <li>• A pothook convenient to install and dismantle</li> <li>• Splice tray could be piled one upon another, flexible to turn</li> <li>• Unique structure, reasonable layout, adequate room for operation</li> <li>• Adjustable clamp seal ring and reinforce configuration</li> <li>• With excellent seal performance, preventing water from entering effectively</li> </ul> |
| APPLICATIONS | <ul style="list-style-type: none"> <li>• Optical Fiber Network</li> <li>• Telecommunications networks</li> <li>• FTTx</li> <li>• OSP</li> <li>• Rack mount in optical distribution frame ODF</li> </ul>  |

<b>Height:</b>	1U (44.4mm)
<b>Packaged dimensions:</b>	480*250*44.4mm
<b>Suitable Adapter:</b>	LC MM
<b>IP Rating:</b>	IP20
<b>Material:</b>	Cold rolled steel Sliding
<b>Capacity of Fiber:</b>	17868
<b>Net weight:</b>	2.2kg
<b>Operating Temp Range:</b>	-40°C to +60°C
<b>Cable Entry 20mm:</b>	4
<b>Material coating:</b>	Electrostatic powder coating

**Designed in accordance with:**

TIA/EIA 568.C, ISO/IEC 11801, EN 50173, IEC 60304, IEC 61754, EN 297-1

**Compliance:**

RoHS, Reach/SVHC



[WWW.JTOPTICS.COM](http://WWW.JTOPTICS.COM)

[INFO@JTOPTICS.COM](mailto:INFO@JTOPTICS.COM)