

Product Name	Part No
24 Fiber MTP Trunk Cable MTP (F) - MTP (F) 300/OM4 50/125µm Multimode Pink Color (OFNP) low loss plenum Cable	JTMPMO424MPSFMPSFXX

**Description**

MTP Trunk Cables are designed for high density application which offers excellent benefits in terms on-site installation time and space saving. The trunk cable assemblies are composed of high quality LSZH jacketed fiber optic cables used in data center, telecom and backbone application for 100G connectivity. Our MTP trunk cables are factory pre-terminated, tested and packed along with the test reports. MTP Trunk Cable are built with highest quality components. 24 Fiber MTP trunk patch cord assemblies are used to interconnect CFP/CFP2/CFP+/CXP transceivers.

- |              |   |
|--------------|---|
| FEATURES     | <ul style="list-style-type: none"> <li>• Lower Insertion Loss &amp; Higher Performance</li> <li>• Complied to ANSI/TIA-568-C.3, IEEE 802.3ba and adheres to ANSI/TIA-942</li> <li>• Low IL and stable signal transmission ensuring your network safety</li> <li>• High-quality MTP connectors and guaranteed by 3D interferometer</li> <li>• 100% factory tested</li> </ul> |
| APPLICATIONS | <ul style="list-style-type: none"> <li>• CFP to CFP+ Connection</li> <li>• CFP+ to CFP+ Connection</li> <li>• CXP to CXP Connection</li> <li>• 10x10G to 10x10G connection</li> <li>• 100G to 100G Interconnection</li> </ul>   |

<b>Connector A:</b>	MTP Female (24 Fiber)
<b>Cable Jacket:</b>	Plenum (OFNP)
<b>Insertion Loss:</b>	0.7dB Max
<b>Polish:</b>	UPC to UPC
<b>Wavelength:</b>	850/1300nm
<b>Return Loss:</b>	≥30dB
<b>Jacket OD:</b>	3.5mm
<b>Installation Tensile Load:</b>	100 N
<b>Operating Temp Range:</b>	-10°C to +70°C
<b>Fiber Mode:</b>	OM4 50/125µm

<b>Connector Make:</b>	US Connect
<b>Connector B:</b>	MTP Female (24 Fiber)
<b>Minimum Bend Radius:</b>	30mm
<b>Storage Temp Range:</b>	-40°C to +85°C
<b>Long-Term Tensile Load:</b>	50 N
<b>Connector Quality:</b>	Standard



[WWW.JTOPTICS.COM](http://WWW.JTOPTICS.COM)

[INFO@JTOPTICS.COM](mailto:INFO@JTOPTICS.COM)