

Product Name	Part No
Lc Lc Om4 Mm Dx Uniboot Pushpull Patch Cord, Lc Pc Lc Pc Om4 Multimode Duplex OFNP Plenum 2Mm Patch Cable	JTPCLCPLCPOM4DXPVXXPPU

### Description

## Lc Lc Om4 Mm Dx Uniboot Pushpull Patch Cord, Lc Pc Lc Pc Om4 Multimode Duplex OFNP Plenum 2Mm Patch Cable

Bidirectional SFP transceiver is intended mainly for connecting high-speed hubs, Ethernet switches, and routers together in different wiring closets or buildings using long cabling runs, and developed to support longer-length on fiber backbones. BIDI Transceiver used only one fiber to transmit and receive optical signal.

FEATURES	<ul style="list-style-type: none"> <li>• Dual data-rate of 1.25Gbps operation;</li> <li>• 1310nm FP laser and PIN photo detector for 40km transmission;</li> <li>• Compliant with SFP MSA and SFF-8472 with duplex LC receptacle;</li> <li>• Digital Diagnostic Monitoring: Internal Compatible with SONET OC-24-ZR-1;</li> <li>• Complied with RoHS</li> </ul>
APPLICATIONS	<ul style="list-style-type: none"> <li>• Gigabit Ethernet</li> <li>• Media converter</li> <li>• Switch to Switch interface</li> <li>• Switched backplane applications</li> <li>• Router/Server interface</li> </ul>
	;

Connector - A:	Uniboot Push-Pull
Connector:	LC to LC
Connector - B:	Uniboot Push-Pull
Insertion Loss:	≤0.35dB
Polish:	UPC to UPC
Wavelength:	850/1300nm
Jacket Material:	PVC
Return Loss:	≥35dB
Jacket OD:	2.0mm
Operating Temp Range:	-40~70°C

<b>Polarity:</b>	A(Tx) to B(Rx)
<b>Minimum Bend Radius:</b>	10D (installed) - 20D (loaded)
<b>Fiber Type:</b>	50/125μm, MM, OM4
<b>Jacket Color:</b>	Pink
<b>Storage Temp Range:</b>	-45~85°C
<b>Cable Retention:</b>	90N
<b>Strength Member:</b>	Aramid



[WWW.JTOPTICS.COM](http://WWW.JTOPTICS.COM)

[INFO@JTOPTICS.COM](mailto:INFO@JTOPTICS.COM)